



DESCRIPTION

Pipe Joint Lubricant is a water dispersible, high performance pipe joint lubricant that has been certified by NSF for use in potable water supply systems. The creamy consistency allows the installer to apply a smooth, consistent coating to both gasket and pipe.

- Mixed fatty acid soap dispersed in glycols and water solvents with a clay pigment filler
- Does not dry out when gaskets are stored in sealed plastic bags or container
- Maintains soft paste consistency and color
- Ideal for all types of pipe (asbestos cement, cast iron, concrete, plastic and clay)
- Does not deteriorate natural or synthetic rubber or plastic gaskets
- Available in quart, gallon and 5 gallon

PRODUCT SPECIFICATIONS

Manufactured from environmentally friendly raw materials

Will not irritate the hands and is not toxic

Appearance (neat)	Soft amber paste
pH (1%)	9.5
Bulk Density	9.3 lb / gal
Free Fatty Acid	1-3%
Total Alkalinity	100 mg KOH / g equivalent
Penetration	300 - 350 1 / 10mm@77°F 200 - 250 1 / 10mm@0°F

ESTIMATED USAGE CHART

PIPE SIZE	LBS. PER 100 JOINTS	PIPE SIZE	LBS. PER 100 JOINTS
4"	3	30"	22
6"	4	36"	28
8"	5	42"	32
10"	6	48"	40
12"	9	54"	45
15"	11	60"	54
18"	13	66"	60
21"	16	72"	67
24"	17	78"	70
27"	19	84"	77

