



HP ADHESIVES LIMITED



**Solvent
Cement**



**Silicone
Sealant**



**Contact
Adhesive**



**Synthetic
Resin
Adhesive**



**Epoxy
Putty**



**Epoxy
Adhesive**



**Masking
& P.T.F.E.
Tape**



**Ball
Valve**



300 for PVC / Regular Bodied



Color
Clear

PVC cement for all classes and schedules with interference fit through 4" (110mm) diameter except schedule 80.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

305 for PVC / Medium Bodied



Color
Clear
Blue
Gray

PVC cement for all classes and schedules with interference fit through 6" (160mm) diameter schedule 80 through 4" (110 mm) diameter

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

311 for PVC / Heavy Bodied



Color
Clear
Gray

PVC cement for all classes and schedules with interference fit, including Schedule 80 through 12" (315 mm) diameter. High-strength formula is ideal for industrial piping systems.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

317 for PVC / Heavy Bodied



Color
Clear
Gray

PVC cement for all classes and schedules with interference fit through 12" (315 mm) diameter (non-pressure applications only up to 18")

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

ALL PRESSURE / Extra Heavy Bodied



Color
Clear

PVC cement for all classes and schedules with interference fit, including Schedule 80 through 18" (450 mm) diameter. Ideal for fabrication of large fittings and applications requiring high gap filling properties.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

314 & 324 for CPVC / Heavy Bodied



Color
Orange
Gray

CPVC cement for all classes and schedules with interference fit through 12" (315 mm) diameter. Industrial quality for non-chemical applications up to 180°F (82°C). Approved for use on CPVC piping systems

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

Gold & 313 for CPVC / Medium Bodied



Color
Yellow
Orange

1 Step Gold CPVC solvent cement for CTS 11 & 13.5 and ASTM sch. 40 & 80 upto 4" dia. ONE STEP CEMENT – formulated to be used without primer if Codes permit.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

S100 PVC Cement



PVC Cement ideal for waterproof joint of rigid PVC pipes & fitting. It is safe for drinking water after complete curing.

Available in size: 100ml & 500ml

325 & 350 for PVC / Medium Bodied



Color
Clear
Blue

Fast setting PVC cement for all classes and schedules with interference fit through 6" (160 mm) diameter, schedule 80 through 4" (110 mm) diameter. Premium formula for wet conditions and/or quick pressurization.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

378 for ABS / Medium Bodied



Color
Clear
Black
Yellow

Fast setting, ABS cement for all classes and schedules with interference fit through 8" (200 mm) diameter. For plumbing application (DWV, sewer, & drain pipe), conduit and foam core.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

394 for ABS-PVC / Medium Bodied



Color
Green

Fast setting, transition cement for all classes and schedules with interference fit through 6" (160 mm) diameter (not for schedule 80). Specifically designed for use on PVC to ABS transition joints in non-pressure systems.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

P-48 for PRIMER / Non Bodied



Color
Clear
Purple

Very aggressive primer for use on PVC and CPVC pipe and fittings. Recommended for commercial and large diameter thermoplastic piping systems, specifically CPVC schedule 40/80. Ideal for use in cold weather applications.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

C-70 for CLEANER




Color
Clear

Specially formulated for removal of oil and grease from the surfaces of PVC, CPVC, ABS and STYRENE pipe and fittings. Recommended for use before priming of pipe and fittings.

Available in size: 118ml (04 OZ) Tin, 237ml (08 OZ) Tin, 473ml (16 OZ) Tin, 946ml (32 OZ) Tin & 5000ml (1.32 GL)

L-90 for LUBRICANT



Custom-formulated, multipurpose lubricants are great for motors, circulators and other pumps, sliding parts, bearings, chains, linkage, or wherever metal lubrication is desired. Non-toxic, soft, paste like material for lubricating bell joint pipe gaskets.

Available in size: 946ml (32 OZ) Tub

CPVC & UPVC Ball Valve



Suitable for drinking water. International quality approval. For use with hot or cold water. Double EPDM O-rings. Teflon seats. Light weight & quick assembly. simple & leak proof joints. Tough & rigid material. Fire resistance. Economical sealed unit

Available in size: 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4"

Gasket Shellac



Gasket shellac compound is a hard setting, slow drying liquid designed to coat, seal and repair most gaskets including felt, paper, rubber and composition type gaskets. It seals metal gaskets and threaded connections for light duty service.

Available in size: 59ml (02 OZ) Bottle

Masking Tape



Resistant to strong solvent and paints. Excellent for industrial applications. Will not tear while removing. No adhesive transfer after removal. No edge lifting

Available in size: 18mm x 20m, 18mm x 30m, 24mm x 30m, 24mm x 40m

P.T.F.E. Tape



Acid & alkali resistant, insulation, soft & flexible. Sealing & locking thread, used in pressurizing the screws of oil, water and air conduits

Available in size: 10M x 12mm x .1mm, 12M x 19mm x 0.1mm

GOLD 3600 Acetoxy Silicone Sealant



INTERIOR & EXTERIOR



DURABLE



ANTIFUNGAL

Customized Color

Gold acetoxy silicone sealant has multipurpose applications such as glazing, weather seal, sheet cladding, curtain walling, general sealing and assembling, drought proofing, sealing door & window frames, skylights, port lights, back lights etc. Automobile and wind shield glass fixing, HVAC & sanitary use.

Available in size: 280 ml

SILVER 3400 Acetoxy Silicone Sealant



INTERIOR & EXTERIOR



DURABLE



ANTIFUNGAL

Customized Color

Silver acetoxy silicone sealant are used for various applications such as glazing, general sealing and assembling, plumbing and sanitary, drought proofing, sealing door & window frames, port lights, back lights and air conditioning systems

Available in size: 260 ml

BRONZE 3200 Acetoxy Silicone Sealant



INTERIOR & EXTERIOR



DURABLE



ANTIFUNGAL

Customized Color

Bronze acetoxy silicone sealant are used for all application such as glazing, general sealing, sanitary and plumbing, drought proofing, windows and doors, air conditioning and many other DIY applications.

Available in size: 260 ml

FAST 3700 Acetoxy Silicone Sealant



INTERIOR & EXTERIOR



DURABLE



ANTIFUNGAL

Customized Color

Fast acetoxy silicone sealant is a high grade sealant specially formulated for special applications such as industrial glazing, sheet cladding, assembling, automobile, water proofing, water exposed applications, auto glass, gasketing for sealing in stone, swimming pools.

Available in size: 280 ml

GLASS & AQUARIUM Silicone Sealant



INTERIOR & EXTERIOR



DURABLE



ANTIFUNGAL

Customized Color

Glass & Aquarium silicone sealant is a high grade sealant specially formulated for aquariums, glass cladding, glazing, auto wind shield fixing, industrial applications, back lights, port lights etc.

Available in size: 280 ml

N7400 NEUTRAL Silicone Sealant



INTERIOR & EXTERIOR



DURABLE



ANTIFUNGAL

Customized Color

Neutral silicone sealant are used for interior and exterior applications like perimetral joints, building and other type of construction. Durable adhesion in range including concrete, masonry, brick, upvc, wood glass and glazed surfaces and some metals used in construction. Suitable for general applications.

Available in size: 280 ml

W7890 Weather Sealant



Customized Color

Weather Sealant are commonly used for external weather sealing. Durable adhesion in range including concrete, masonry, brick, upvc, wood glass and glazed surfaces. Used in some metals for construction without danger of corrosion from the sealant.

Available in size: 300 ml

ACRYLIC Sealant



Customized Color

Acrylic sealant are used in the building industry for filling joints between wood, metal window frames, upvc doors & windows, concrete brick work, joints between concrete and ceiling elements, between wall and ceiling skirting boards, window sills, sealing around pipe joints, sealing duct work, wall cracks filling, aerated concrete for inside and outside applications.

Available in size: 280 ml

EPOXY ADHESIVE



STRONGTITE Epoxy Adhesive is high strength, multi-purpose epoxy adhesive. Ideal for artificial jewellery, fixing marble, granite and wood, sand broadcasting and grouting steel railings

Available in size: 450g, 900g, 1.8kg, 9kg

EPOXY ADHESIVE



STRONGTITE Epoxy Adhesive is high strength, multi-purpose epoxy adhesive. Ideal for artificial jewellery, fixing marble, granite and wood, sand broadcasting and grouting steel railings

Available in size: 6g, 12g, 36g, 90g, 180g

General Purpose Epoxy Putty



It can be used in sealing, gripping, joining and insulating variety of surfaces like ferrous and non-ferrous metals, porcelain, ceramic, marble, granite, ivory, asbestos, glass, wood, leather, certain plastics etc.

Available in size: 25g, 50g, 75g, 90g, 250g & 1kg

Fast & Sanitary Epoxy Putty



It can be used in sealing, gripping, joining and insulating variety of surfaces. Will bond to various substrates such as fiberglass, metal, wood, concrete, ceramic, glass etc. After the final cure, it will not yellow when exposed to U.V. and can be drilled, tapped, machined, ground or filed.

Available in size: 25g, 50g, 75g, 90g, 250g & 1kg

SF-555 & E-555 Contact Adhesive



SF-555 is brushable adhesive which offers high coverage, high adhesion, ready to use, resistant to the effect of water. The product is ideally used for applications such as bonding of luggage and trolley bags, sole, casual shoes, safety shoes, mattresses, sofas, chairs, seat covers.

Available in size: 100ml, 200ml, 500ml, 1litre, 5litre, 15litre, 30litre

SF-777 & E-777 Contact Adhesive



SF-777 is brushable grade ready to use synthetic rubber based contact adhesive providing high coverage, high adhesion and is resistant to the effect of water. The product is ideally used for the bonding of seat cover, mattress, sofas and chairs.

Available in size: 100ml, 200ml, 500ml, 1litre, 5litre, 15litre, 30litre

SF-999 Contact Adhesive



SF-999 is synthetic rubber based contact adhesive meant for excellent coverage. The product is ideally used for bonding AC ducts, wooden crafts, PVC flooring & furniture. It has high bonding strength with fast-drying and good tack properties.

Available in size: 100ml, 200ml, 500ml, 1litre, 5litre, 15litre, 30litre

SF-HEAT O PRO Contact Adhesive



SF-HEAT O PRO is a multipurpose fast bonding contact adhesive having high heat resistant, high bond strength, long open time, spreads easily, suitable for most substrates. The product is used for bonding in various industries like furniture, footwear, handicrafts and automotive.

Available in size: 100ml, 200ml, 500ml, 1litre, 5litre, 15litre, 30litre

SP-604 Contact Adhesive



SP-604 is a synthetic rubber based sprayable adhesive which is ideally used for bonding of Foam to Foam and Foam to Fabric in furniture which are exposed to low wear & tear. This product is versatile making it favorites with upholsters work. It provides excellent Initial bonding, low viscosity, high strength and spreads easily.

Available in size: 15litre, 30litre

SP-607 Contact Adhesive



SP-607 is a high-performance synthetic rubber based sprayable adhesive specially designed for instant bonding of foam to foam applications foam to bonded foam, rexine, fabric to foam/ rexine, leather to leather/ foam or rexine, metal to foam, Foam to EPE sheet having low viscosity high strength properties .

Available in size: 15litre, 30litre

SP-SFR Contact Adhesive



STRONG FIX SP-SFR is an improved version sprayable adhesive developed specially to achieve heat resistance and non-flammable properties. Polychloroprene based rubber suitable grade are selected. Specially additives are added to increase the heat resistance & non-flammable property.

Available in size: 15litre, 30litre

POWER-PVA Synthetic Resin Adhesive



POWER-PVA is a PVA based specially modified cross-linked adhesive. It provides excellent adhesion to laminate/wood/veneer/particle board/block board to wood/ply/flush door/MDF/HDF. It also offers very high interior water-resistivity and good bonding in lamination with all grades of wood after optimum curing.

Available in size: 500g, 1kg, 2kg, 5kg, 10kg, 20kg, 50kg

QuikR3 Synthetic Resin Adhesive



HP QuikR3 is a fast setting specially modified copolymer. It provides excellent adhesion to laminate/wood/ veneer/block board to wood/ply/flush door/MDF/HDF. It also offers hot water-resistance and excellent bonding in lamination with all grades of wood after optimum curing.

Available in size: 500g, 1kg, 2kg, 5kg, 10kg, 20kg, 50kg

GOLD Synthetic Resin Adhesive



HP GOLD is synthetic resin based adhesive having transparent and glossy film properties. It is non flammable and non toxic in nature. These are used by furniture manufacturer, OEM for industrial usage as general purpose wood working applications having more coverage area and providing better strength while joining laminates to particle boards, decorative laminates, wood to wood & ply to wood

Available in size: 500g, 1kg, 2kg, 5kg, 10kg, 20kg, 50kg

Black & White Liquid Sealant



Easy to apply. Plugs leakage 100% .Most reliable for pipe joints. Suitable for pipes carrying solvents & chemicals

Available in size: 40g, 100g, 200g, 500g & 1kg



HP ADHESIVES LIMITED

G-11, Unique House, Chakala, Andheri (E), Mumbai - 400099. Maharashtra, India.

Ph: +91-22-68196300

Visit us @ www.hpadhesives.com

Email: info@hpadhesives.com