



 **STRONG FIX**TM

CONTACT ADHESIVE



BRUSHABLE



SPRAYABLE



SF-222

Appearance:	Yellowish Liquid
Coverage:	5-6 sq. meter per litre
Drying Time:	20 sec. to 30 sec.
Tack Time:	05 min. to 15 min.
Density:	0.84± 0.02gm/ml



STRONG FIX SF-222 is synthetic rubber based brushable adhesive which spreads easily, provides excellent coverage, high bonding strength and offers superior sticking power. The product is versatile and bonds most materials like foam and fabric, seat covers. It is heat resistant and flexible once cured.

Available in size: 200ml, 500ml, 1L, 5L, 15L, 30L, 50L & 200L



SF-555

Appearance:	Yellowish Liquid
Coverage:	5-6 sq. meter per litre
Drying Time:	20 sec. to 30 sec.
Tack Time:	05 min. to 15 min.
Density:	0.84± 0.02gm/ml



STRONG FIX SF-555 is brushable grade synthetic rubber based contact adhesive which offers high coverage, high adhesion, ready to use, resistant to the effect of water. The product is ideally used for applications such as bonding of luggage and trolley bags, sole, casual shoes, safety shoes, mattresses, sofas, chairs, seat covers.

Available in size: 200ml, 500ml, 1L, 5L, 15L, 30L, 50L & 200L



SF-111

Appearance:	Yellowish Liquid
Coverage:	5-6 sq. meter per litre
Drying Time:	20 sec. to 30 sec.
Tack Time:	05 min. to 10 min.
Density:	0.84± 0.02gm/ml



STRONG FIX SF-111 is brushable grade synthetic rubber based contact adhesive which offers high coverage, high adhesion, ready to use, resistant to the effect of water. The product is ideally used for applications such as bonding of luggage and trolley bags, sole, casual shoes, safety shoes, mattresses, sofas, chairs, seat covers.

Available in size: 200ml, 500ml, 1L, 5L, 15L, 30L, 50L & 200L



SF-777

Appearance:	Dark Brownish Liquid
Coverage:	4-5 sq. meter per litre
Drying Time:	20 sec. to 30 sec.
Tack Time:	20 min. to 30 min.
Density:	0.82± 0.02gm/ml



STRONG FIX SF-777 is brushable grade ready to use synthetic rubber based contact adhesive providing high coverage, high adhesion and is resistant to the effect of water. The product is ideally used for the bonding of seat cover, mattress, sofas and chairs.

Available in size: 200ml, 500ml, 1L, 5L, 18L, 30L, 50L & 200L



SF-555 FW / 777 FW

Appearance:	Yellowish Liquid
Coverage:	5-6 sq. meter per litre
Drying Time:	20 sec. to 30 sec.
Tack Time:	SF 555 FW- 05 min. to 25 min. SF 777 FW- 05 min. to 45 min.
Density:	0.84± 0.02gm/ml



STRONG FIX SF-555(FW) & 777(FW) is brushable grade synthetic rubber based contact adhesive which offers high coverage, high adhesion, ready to use, resistant to the effect of water. The product is ideally used for applications such as bonding of luggage and trolley bags, sole, casual shoes, safety shoes, mattresses, sofas, chairs, seat covers.

Available in size: 200ml, 500ml, 1L, 5L, 15L, 30L, 50L & 200L



SF-HEAT O PRO

Appearance:	Yellowish Liquid
Coverage:	3-5 sq. meter per litre
Drying Time:	10 sec. to 20 sec.
Tack Time:	up to 05 min.
Density:	0.86± 0.03gm/ml



STRONG FIX SF-HEAT O PRO is a multipurpose fast bonding brushable grade synthetic rubber based contact adhesive having high heat resistant, high bond strength, long open time, spreads easily, suitable for most substrates. The product is used for bonding in various industries like furniture, footwear, handicrafts and automotive.

Available in size: 200ml, 500ml, 1L, 5L, 15L, 30L, 50L & 200L



SP-601

Appearance:	Brownish Liquid
Coverage:	80 to 100 gms/meter ²
Drying Time:	20 sec. to 30 sec.
Tack Time:	03 min. to 10 min.
Density:	1.00± 0.20gm/ml



SP-601 (Sprayable) is multipurpose adhesive. Where more bonding strength is required. It is specially used in furniture work and foam bonding. It provides excellent Initial bonding, low viscosity, high strength and spreads easily.

Available in size: 8.5kg, 30litre



SP-604

Appearance:	Brownish Liquid
Coverage:	80 to 100 gms/meter ²
Drying Time:	20 sec. to 30 sec.
Tack Time:	10 min. to 20 min.
Density:	0.80± 0.02gm/ml



SP-604 is a synthetic rubber based sprayable adhesive which is ideally used for bonding of Foam to Foam and Foam to Fabric in furniture which are exposed to low wear & tear. This product is versatile making it favorites with upholsters work. It provides excellent Initial bonding, low viscosity, high strength and spreads easily.

Available in size: 5litre, 4.5litre, 1litre, 15litre, 30litre



SP-605

Appearance:	Brownish Liquid
Coverage:	80 to 100 gms/meter ²
Drying Time:	10 sec. to 20 sec.
Tack Time:	15 min. to 30 min.
Density:	0.84± 0.02gm/ml



SP-605 is synthetic rubber based sprayable multi-purpose adhesive. The product is ideally used in the automobile sector for bonding of PVC and carpet flooring, ply to felt and felt to Eva. The product has low viscous, high strength, instant bonding properties which provide higher coverage.

Available in size: 15litre, 30litre



SP-606

Appearance:	Colourless liquid
Coverage:	10 – 12 sq. meter PL
Drying Time:	10 sec. to 20 sec.
Tack Time:	02 min. to 05 min.
Density:	0.84± 0.02gm/ml



STRONG FIX SP-606 is colourless viscous liquid of Spraying viscosity. STRONG FIX SP-606 is formulated after intense R&D efforts to address diverse application needs of the industry. It is an improved version sprayable adhesive developed specially for PU foam repair purpose and general bonding where colour issue is major problem. 1. Polychloroprene based rubber suitable grade are selected.

Available in size: 15litre, 30litre



SP-607

Appearance:	Brownish Liquid
Coverage:	80 to 100 gms/meter ²
Drying Time:	10 sec. to 20 sec.
Tack Time:	10 min. to 20 min.
Density:	0.80± 0.20gm/ml



SP-607 is a high-performance synthetic rubber based sprayable adhesive specially designed for instant bonding of foam to foam applications foam to bonded foam, rexine, fabric to foam/ rexine, leather to leather/ foam or rexine, metal to foam, Foam to EPE sheet having low viscosity high strength properties It can also be used for vinyl flooring and carpet laying application. It is heat resistant and flexible once cured.

Available in size: 1litre, 5litre, 15litre, 30litre



SP-609

Appearance:	Brownish Liquid
Coverage:	8 – 10 sq. meter per liter
Drying Time:	10 sec. to 20 sec.
Tack Time:	15 min. to 30 min.
Density:	0.82± 0.20gm/ml



STRONG FIX SP-609 is Yellowish viscous liquid of Spraying viscosity. STRONG FIX SP-609 is formulated after intense R&D efforts to address diverse application as per Mattresses & furniture industry need.

Available in size: 500ml, 1litre, 5litre, 15litre, 30litre, 50litre



SP-SFR

Appearance:	Yellowish Brown Liquid
Coverage:	6-8 sq. meter per litre
Drying Time:	10 sec. to 20 sec.
Tack Time:	10 min. to 20 min.
Density:	1.20± 0.02gm/ml



STRONG FIX SP-SFR is an improved version sprayable adhesive developed specially to achieve heat resistance and non-flammable properties. Polychloroprene based rubber suitable grade are selected. Specially additives are added to increase the heat resistance & non-flammable property. The product is non-toxic in nature as it benzene free it can be used by spray or brush

Available in size: 15litre, 30litre



SP-BM

Appearance:	Yellowish Liquid
Coverage:	8-10 sq. meter per litre
Drying Time:	20 sec. to 40 sec.
Tack Time:	10 min. to 20 min.
Density:	0.82± 0.02gm/ml



SP-BM is a synthetic rubber based sprayable high strength, high viscosity cross-linking adhesive which is ideally used by automobile industries for applications in a variety of substrates like bonding of high-density foam, thermal insulation, non-woven, plastics, plywood and timber log. The product is non-toxic in nature as it benzene free it can be used by spray or brush

Available in size: 5litre, 15litre, 30litre



SP-AMR

Appearance:	Yellowish Liquid
Coverage:	80 to 100 gms/meter ²
Drying Time:	10 sec. to 20 sec.
Tack Time:	02 min. to 05 min.
Density:	0.84± 0.02gm/ml



STRONG FIX SP-AMR is improved version sprayable adhesive developed specially for Automobiles sector and Canopies Industries (Generator) to achieve proper heat resistance.

- 1) Polychloroprene based rubber suitable grades are selected.
- 2) Special additives are added to increase the heat resistance.

Available in size: 15litre, 30litre



We also manufacture

Solvent Cement, Silicone Sealant, PVA/White Glue, FRP Manhole Cover, Black & White Sealant, Shellac, Epoxy Putty, Epoxy Adhesive, Masking & P.T.F.E. Tapes etc.



HP ADHESIVES LIMITED

G-11, Unique House, Chakala, Andheri (E),
Mumbai - 400099, Maharashtra, INDIA
Ph: +91-22-68196300

Visit us @ www.hpadhesives.com
For Sales: sales@hpadhesives.com
For General Inquires: info@hpadhesives.com